

# BETAPRIME™ 5504G All-in-One Primer



## “No Shake” means one less worry, whether your installation is mobile or in the shop

- Optimizes installation process – elimination of shaking step makes process easier, safer, faster
- Fast flash-off (dry) time helps eliminates excessive waiting time following application
- One primer for all common aftermarket substrates: glass, nicks and scratches, paint, encapsulations (PUR, PVC, PAAS and metal) and cut bead
- Reduces cost and optimizes inventory by eliminating redundant products
- Effective in treating larger bare metal areas – allows for corrosion treatment in the field
- Works in a wide range of weather and temperatures from -5°C to 40°C
- Ideal for mobile installations





## BETAPRIME™ 5504G – “No-Shake” all-in-one, black primer optimizes and simplifies installation process

Replacing windcreens is now even simpler with BETAPRIME™ 5504G All-in-One “No-Shake” Primer. BETAPRIME™ 5504G can be used for priming both auto glass and cut bead. You can also use it on bare metal, paint and encapsulations, such as PUR, PVC and PAAS.

### Saves time and money

BETAPRIME™ 5504G All-in-One “No-Shake” Primer eliminates the “shaking” step for a sure, easy and fast installation. It saves material costs and reduces installation time because you only need to buy and apply one product. Because BETAPRIME™ 5504G can be used on virtually all substrates, it can reduce costly mistakes, such as applying the wrong primer to the wrong part.

Other time-saving advantages include fast flash-off (dry) time that helps eliminate excessive waiting time following application.

### Promotes strong, long-lasting bonds

Using an all-in-one primer is not a compromise. BETAPRIME™ 5504G has been tested in thousands of applications on a wide range of windcreens and with all BETASEAL™ adhesives. BETAPRIME™ 5504G All-in-One “No-Shake” Primer is black to provide excellent UV protection to the adhesive. This helps bonds last longer.


## Easy-to-use: Clean, Prime and Bond

BETAPRIME™ 5504G All-in-One “No-Shake” Primer is part of a simple, superior system that includes BETACLEAN™ 3300 cleaner and all BETASEAL™ auto glass adhesives. Just three easy steps: clean, prime and bond.

## Use in a wide range of temperatures and weather

Use in a wide range of temperatures and weather. Inclement weather is much less of a problem with BETAPRIME™ 5504G. It works in both cold and warm temperatures, -5°C to 40°C, making it the ideal system for mobile installations.

## BETAPRIME™ 5504G drying time



[dupont.com](http://dupont.com)



DuPont™, the DuPont Oval Logo, BETASEAL™, BETACLEAN™, BETABRADE™ and BETAPRIME™ are trademarks or registered trademarks of DuPont or its affiliates. Copyright © 2019 DuPont de Nemours Inc. All rights reserved.

Form No. 001-20076-OIA0419