

# DuPont™ Cyrel® DigiFlow 2000 ECLF

## State-of-the-Art Exposure Unit



[View Hi Res Image](#)

### DuPont™ Cyrel® DigiFlow 2000 ECLF



[View Hi Res Image](#)

### Floor Plan



Play Video



Download latest version

DuPont Packaging Graphics continues to be a global technology leader in the development and supply of flexographic printing systems. Our R&D team continues to develop innovative new solutions to help our customers expand their business by taking advantage of new and profitable opportunities in the growing flexographic packaging market. The DuPont Packaging Graphics portfolio of products includes DuPont™ Cyrel® brand photopolymer plates ([analogue](#) and [digital](#)), Cyrel® platemaking equipment, [Cyrel® round sleeves](#), [Cyrel® plate mounting systems](#) and the revolutionary [Cyrel® FAST thermal system](#).

DuPont™ Cyrel® Systems: Higher quality at high speed.

**The DuPont™ Cyrel® DigiFlow 2000 ECLF is designed with customer needs in mind; it is easy to install, support, maintain and operate. It is robust, extremely cost effective and reliable.**

### DuPont™ Cyrel® DigiFlow 2000 ECLF

#### Benefits

- Maximum plate size 1,070 x 1,530 mm (42" x 60")
- Top lift design
- High power UV-A fluorescent tubes
- Individual lamp sensor measurement tool
- Exposure in standard digital dot mode or DigiFlow mode
- Optimised temperature controlled exposure bed
- Optimum productivity

#### Product Features

DuPont™ Cyrel® DigiFlow 2000 ECLF exposes high quality photopolymer plates up to a format of 1,070 x 1,530 mm (42" x 60").

Unique to this exposure unit is the high power UV-A output with variable intensity level controls. In addition, it includes the DigiFlow mode; a controlled exposure environment designed to produce the exact 1:1 reproduction that is necessary to optimise solid screening programs for enhanced solid ink density.

The vertical lift exposure lid allows easy and convenient access to the cooled exposure bed. The unit is configured with 34 UV-A high power fluorescent tubes with built-in reflectors and includes a new lamp sensor measurement tool for easy calibration. The DigiFlow 2000 ECLF also includes an optimised temperature controlled bed, including a closed loop system to monitor and control exposure bed temperature for predictable and consistent exposures. A built-in light integrator ensures consistent exposure throughout the life of the lamps. The unit is controlled through a digital touch pad with over 50 different exposure set-ups which can be stored for quick and easy recall.

# DuPont™ Cyrel® DigiFlow 2000 ECLF

## State-of-the-Art Exposure Unit

Technical Data		
General	Details	Other Notes
<b>Equipment Name</b>	DuPont™ Cyrel® DigiFlow 2000 ECLF	
<b>SAP Article Number</b>	D15093072	
<b>Plate Thickness</b>	0.5 mm to 7.0 mm	0.019" to 0.27"
<b>Max. Nominal Plate Width</b>	1,070 mm (42")	
<b>Max. Nominal Plate Length</b>	1,530 mm (60")	
<b>UV-A Tubes Wave Length Peak</b>	364 nm	With reflector
<b>UV-C Tubes Wave Length Peak</b>	250 nm	
<b>Electrical (Field Configurable)</b>	360 / 440 Volt – 50 / 60 hz 207 / 243 Volt – 50 / 60 hz	3Ph / N / PE 3Ph / PE
<b>Power (nominal)</b>	21 kW	
<b>Current (Nominal Load)</b>	33.5 Amp @ 400 Volt / 230 Volt	
<b>Connecting Wires</b>	400 Volt configuration; 230 Volt configuration	5 x 6 mm <sup>2</sup>
<b>Grounding</b>	≤ 0.1 Ω	
<b>Environmental Data</b>	Temperature range: 17°C to 28°C (63°F to 80.6°F)	Relative humidity from 10% to 80% non-condensing
<b>Compressed Air Supply</b>	6–10 bar	200 l / min. Pressure dew point 3°C, max. residual intake oil content of ≤0.01 mg/m <sup>3</sup>
<b>Dimensions</b>	<b>Uncrated</b> L 2,304 mm (90.7") W 2,039 mm (80.2") H 2,120 mm (83.5")	<b>Crated</b> 3,200 mm (126.0") 2,200 mm (86.6") 2,533 mm (99.7")
<b>Weight</b>	1660 kg (3,659.7 lbs)	2,200 kg (4,850.2 lbs)
<b>Colour</b>	DuPont Grey & DuPont Red	

For more information on DuPont™ Cyrel® or other DuPont Packaging Graphics products, please contact your local representative:

[www.cyrel.eu](http://www.cyrel.eu)

DuPont de Nemours (Deutschland) GmbH  
DuPont Electronics & Communications  
Hugenottenallee 175  
63263 Neu-Isenburg  
Germany  
Tel: +49 (0) 6102 18 1592

DuPont (U.K.) Limited  
DuPont Electronics & Communications  
Wedgwood Way, Stevenage  
Hertfordshire SG1 4QN  
United Kingdom  
Tel: +44 (0) 1438 73 4863